

EUCO QUARTZ

INTERIOR AND EXTERIOR TEXTURED QUARTZ PAINT

Description **EUCO QUARTZ** is a decorative exterior and interior coating which is a carefully controlled blend of fillers, fine, medium or coarse quartz particles, resins and pigments dispersed in a specifically formulated flexible emulsion. **EUCO QUARTZ** may be applied with a special roller to produce a varying degree of textured finish or with a paint brush for a smooth finish. However a plastering machine will spray the material at a faster rate which is ideal for use in commercial buildings, town houses, or ware houses.

Properties

- 1- Gives a decorative finishing for facade, building entrance ... etc.
- 2- Resists different weathering conditions, UV rays for several years.
- 3- Covers cracks up to 1 mm.
- 4- Could be applied directly on concrete, bricks, wood surfaces and plastering.
- 5- Available in white and other stable colour.
- 6- It is ready to use with no other additives.
- 7- Easy to use and can be applied with many application possibilities.

Application

- 1- Preparation : all surfaces to which **EUCO QUARTZ** is to be applied must be sound. Remove all loose and unsound materials fill cracks with standard filler and allow to dry.
- 2- Application. : **EUCO QUARTZ** is applied one coat using the following procedure:
 - 1- If the surface is very porous apply. **EUCO QUARTZ** before painting.
 - 2- Stir well before use.
 - 3- Spread **EUCO QUARTZ** on to the surface by using roller, brush or steel spatula.
 - 4- The degree of texture will be dependent on the roller design and according to the kind of roller (wool, cotton, sponge) .
 - 5- The roller should be well coated, but not over loaded, as this could cause dropping or spillage.

Consumption 1-2 kg/m² depends on grain size and required thickness.

| | |
|--------------------|---------------------------------------|
| Shelf life | two years |
| EUCO QUARTZ | is available in three grades |
| Fine | application by roller, spray or brush |
| Medium | application by roller or spatula. |
| Coarse | application |
| Package | 25-30 kgs drums. |