

EUCOCURE BR
Cure-seal hardener

Description **EUCOCURE BR** is a cure seal hardener based on inorganic silicates .

Main Purpose To protect fresh concrete surfaces from the undesirable effects associated with too rapid evaporation of surface moisture .Provides a denser and harder surface with increased resistance to abrasion .Floors treated with **EUCOCURE BR** will not be affected when subsequently painted and will eliminate problems of dusting when concrete surfaces are subjected to heavy traffic .A treatment with **EUCOCURE BR** will also reduce permeability of concrete to water and other liquids as oil etc. .

Advantages **EUCOCURE BR** provides a cost saving method of protecting all fresh concrete and does not contain wax , oils or resins and leaves no residue **EUCOCURE BR** penetrates the concrete surface and reacts chemically with free lime present into an insoluble product .

Standards Complies with ASTM C 309,DIN and SIA standards .

Properties	Appearance	liquid
	Specific gravity	1,4
	Colour	dark blue
	Flash point	not applicable
	Shelf life	well closed up to 2 years

Application **EUCOCURE BR** may be applied with either hand or spray equipment .Wash equipment with clean water immediately after using . Avoid contact with skin or eyes .For new concrete **EUCOCURE BR** should be applied immediately after the final trawling .Old concrete should be thoroughly cleaned before treatment to allow **EUCOCURE BR** to penetrate .

Consumption Dilute 1 part of **EUCOCURE BR** with 3-4 parts of water .After dilution the consumption is about 10 m2 / per liter .

Remarks When **EUCOCURE BR** is applied before the final trawling , it may accelerate the initial setting .
EUCOCURE BR should not be spilled or sprayed on glass or marble like surfaces in this case flush immediately with water .Avoid contact with skin or eyes

