

## **EUCOTEX VINYL TILES ADHESIVE**

**Description** Non toxic adhesive formulated to meet the high class specifications, easily applied even on vertical surfaces. The filling effect of the adhesive makes it most suitable for bonding on uneven substrata; the tacky and additive contents improve the adhesion power at low and high temperatures.

The product can be used either on new or old floors without any other preliminary treatment than ordinary cleaning.

**EUCOTEX** can be used on concrete, cement tiles, wood and parquet flooring.

**Advantages**

- Keeps tiles effectively in place during life time.
- Ready mixed; easy to use.
- No priming or other preliminary treatment necessary.
- Can be used for new and old floors.
- Bonds to variety of materials.
- High coverage-economic in use.
- Water resistant when cured.

**Floor preparation** The surface must be clean dry and free from dust, dirt, oil or grease and loose materials, remove dust and friable materials with stiff brush, remove oil or grease with a suitable detergent .Very porous sub floors should be primed with adhesive solution turpentine.

**Application** Apply **EUCOTEX** using a notched trowel with 1.5-2.5 mm, deep triangular notches at 5 mm centers. The flooring material normally placed during the wet adhesive waiting time of 5-15 minutes. press the P.V.C. tiles firmly onto the adhesive and roll in both directions with a heavy roller to ensure adequate contact, transfer of adhesive and elimination of air pockets. Remove surplus adhesive with a damp cloth or sponge. Installing sheet vinyl tiles on non porous surfaces:-Leave the adhesive (after applying as above) for 20 to 30 minutes fixing flooring material until it has become very tacky to the touch. Then proceed as before, position tiles or sheet with care. Adhesive will remain, pressure sensitive for 4 hours.

**Consumption** From 3-4 m<sup>2</sup>/kg depending on porosity of the surface.

**Package** Drums containing 20 kg.